

LIRO43048A Lithium Ion Battery

Brief Datasheet

1 Basic Specification

Nominal Voltage		3.7V
Nominal Capacity		600mAh (0.2C discharge)
Internal Resistance		≤60mΩ
Maximum Charge Current		1C
Maximum Discharge Current		1C
Charge Method		CC/CV (Constant Current/Constant Voltage) 0.5C for 5hrs; 1.0C for 2.5hrs
Charge Voltage		4.20V
Discharge cut-off voltage		3.0V
Operation Temperature	Charge	0°C to 45°C
	Discharge	-20°C to 55°C
Storage Temperature		-5°C to 35°C
Cycle life		300 Cycles
Weight		Approx. 14.5g
Voltage of Shipment		3.70V-3.90V (about 50% capacity)

*1C =1 Capacity

**"A" stands for Aluminium case

2 MAIN FEATURES

- Long shelf-life and low self-discharge rate.
- Easily customized, Energy density, High capacity.

3 WARNING

- Do not overcharge, force charge, short circuit, disassemble, deform, heat or place the battery near a direct flame. Any of the above actions could cause it to ignite, explode or become damaged.
- Keep this battery out of the reach of children.
- When storing the battery or throwing it away, be sure to cover with tape.

Autec Battery LTD.
 Add : 667 E. Cochran St. Simi Valley, CA 93065
 Tel: 805-522-0888 Fax: 805-522-8777
 E-mail : battery@autec.com Website: www.autecbattery.com

